

SUSPENDED PLATFORM ACCESUS BASIC "S" MINIMUM WIDTH

TECHNICAL INFORMATION

Accesus Basic "S" suspended access platform with minimum width and special raised bracket, ideal for small spaces (light wells, confined spaces...).

The special feature of the Accesus Basic "S" car is that it is the suspended car with the smallest floor plan dimensions on the market. The Accesus Basic "S" cabin is fully compatible with all the cabins in the standard Basic range.

Suspension cabin for lifting persons and loads in accordance with EN 1808.

The Accesus Basic "S" suspended platform consists of the same components (except for the bracket) as the Basic suspended platform in 0.8, 1.2 and 1.6 m length.

The components are lightweight, easy to assemble, store and transport. The assembly is carried out by means of screws for maximum safety.

The parts are small in size and allow passage through places that are difficult to access, such as lifts, interior courtyards, etc...

Minimum space where it fits when disassembled (manhole) is Ø670 mm (maximum size of the piece is 640 mm). AVAILABLE ON REQUEST FOR Ø520 MM MANHOLE.

The Accesus Basic "S" suspended platform is equipped with an electric hoist with a capacity of 500 kg, offering maximum safety and performance for lifting people.

The Accesus Basic suspended access platform is compatible with all Accesus suspension systems.

Overall dimensions: 0.80 / 1.20 / 1.60 x 0.63 x 2.67 m.



SAFETY DEVICES

- Overload control.
- Working and safety cable.
- Cable safety coefficient >8.
- 1 m high handrails.
- Perimeter skirting.
- Non-slip floor.
- CE marked.
- Approved for lifting people.

TECHNICAL CHARACTERISTICS

ACCESUS BASIC "S" SUSPENDED PLATFORM	
Maximum load capacity	120 / 240 kg
Number of persons	1 / 2
Maximum working height	Unlimited
Maximum cabin length	1,60 m
Minimum cabin length	0,80 m
Height of handrails	1 m
Minimum space where it can be disassembled	Ø 0,67 m

SUSPENDED PLATFORM ACCESSUS BASIC "S" MINIMUM WIDTH

LOAD-BEARING CAPACITY

	Platform length (m)	0.8	1.2	1.6
<i>Accessus Basic "S" Cabin</i>	Load capacity (kg)	120	240	240
	Number of persons	1	2	2



COMPOSITION

Platform length (m)	0.8	1.2	1.6
0.8m floor	1	0	0
1.2m floor	0	1	0
1.6m floor	0	0	1
Lifting bracket	0	0	0
Connecting bracket	0	0	0
Basic "S" stirrup	1	1	1
Limb lyre	2	2	2
Lateral support 0.8m	2	0	0
Lateral support 1.2m	0	2	0
Lateral support 1.6m	0	0	2
Handrail 0.8m	2	0	0
Handrail 1.2m	0	2	0
Handrail 1.6m	0	0	2

GENERAL DIMENSIONS





